

2-6 Function IP Stainless Transmitter

REPLACEMENT TRANSMITTER

92S06TX 2-6 Function IP Transmitter – Stainless Steel Keypad



CONTENTS

1 x IP Transmitter Stainless
1 x Lanyard
1 x Instructions

TRANSMITTER SPECIFICATION

ENCLOSURE

Material Stainless Steel Keypad
Functions 6
Identification Specially printed label for each button available at request.

RF

Modulation 2-GFSK. Gaussian Frequency Shift Keying
Frequency 433.050 MHz to 434.790 MHz
Channels 1
Channel Selection Fixed
Technology Hand-held Transmitter
Temperature Range -10° C to + 40° C (13° F to + 104° F). Use Lithium for lower temperatures
Range 60m (200ft)
Aerial Internal – printed on PCB
Transmitted power 1mW Typical

INDICATOR

Type 1 x Red LED
Off Transmitter OFF (The STOP Button has been pressed and released)
Slow flash Transmitter ON and ready for use (The SET Button has been pressed and released)
On Transmitting (A STOP, SET or Function Button is being pressed)
Fast flash Transmitting – Indication that the battery will need replacing soon

POWER

Batteries 4 x AAA Alkaline Manganese in holder (6 Volts)
Quiescent Current 15µA
Current Transmitting 20mA

PROTECTION

IP Rating 65
Registration codes Over 16 million

INDICATOR

Type 1 x Red LED
Off Transmitter is OFF and in standby mode
Slow flash Transmitter is ON and ready for use (The SET Button has been pressed and released)
On Transmitting (A STOP, SET or Function Button is being pressed)
Fast flash Transmitting – Indication that the battery will need replacing soon

COMPLIANCE

FCC FCC CFR 47-part 15.231
433.9MHz
IC ISED RSS-210 Issue 8
433.9MHz
RoHS Directive 2011/65/EU